

According to Attachment II EC Reg. 1907/2006 (REACH)

SiLiglam N	IATURE -	Type P Co	olor shades	
First created on:	2017-02-14	Updated on:	2022-03-23	
Next inspection on:	2022-12-31	Printed on:	2022-03-23	Version: V4/2022

Note: The product is an object defined as an article in the Regulation (EC) No. 1907/2006 (REACH) Art. 3 Par. 3, not classified as dangerous or not containing substances classified as dangerous, so there is no obligation to issue a safety data sheet according to the Regulation (EC) No. 1907/2006 Art. 31 (Requirements for safety data sheets). The following information complies with the obligation according to Art. 32 (for substances on their own or in preparations for which a safety data sheet is not required) and was issued following the structure by Annex II.

1. Identification of the substance / the preparation / the product and identification of the company

1.1 Identification of the substance / the preparation / the product

Trade name: SiLiglam NATURE Type P Colour shades

1.2 Application of the substance / the preparation / the product

To be used as: Unsubscribed use: Effect material for cosmetics unknown

Sigmund Lindner GmbH

1.3 Company identification

Manufacturer / Supplier:

	95485 Wai Phone: Fax: Web:	ensteinacher Str. 38 mensteinach / GERMANY +49-9277-9940 +49-9277-99499 www.sili.eu
	E-Mail:	<u>reach@sili.eu</u>
Information provided by:		el Dressler (Head of Quality) Id Schneider (Quality Manager)

1.4 Emergency Call

Emergency information:

Phone: +49-9277-9940

This telephone number can be reached during Office Hours (CET):Monday - Thursday:7.00 AM - 4.30 PMFriday.7.00 AM - 1.00 PM

2. Possible dangers

2.1 <u>Classification of the substance or mixture</u>

Not classified according to Regulation (EG) No. 1272/2008 (CLP).

2.2. <u>Labeling elements</u>

Not subject to labeling according to Regulation (EG) No. 1272/2008 (CLP).

2.3. Additional danger advice

No risks from this product regarding human health or environment are apparent. We therefore have no knowledge of chronic or skin irritating effects when physical contacts have occurred.



Sigmund Lindner

According to Attachment II EC Reg. 1907/2006 (REACH)

SiLiglam NATURE - Type P Color shadesFirst created on:2017-02-14Next inspection on:2022-12-31Printed on:2022-03-23

Version: V4/2022

3. Composition / detailed information on the ingredients

- 3.1 <u>Substance</u> Not relevant.
- 3.2 <u>Mixtures</u> Description:

Solid made of coated polylactic acid film

3.3 Ingredients

Substance Name	Classification	Weight	CAS Nº	EC N°	REACH Reg. N°
Coating *)	no hazardous substance	2.0 %	none	none	no registration
CI 77491	no hazardous substance		1309-37-1	215-168-2	01-2119457614-35
CI 77510	Aquatic Chronic 4; H413		25869-00-5	247-304-1	01-2119555296-32
CI 77492	no hazardous substance		51274-00-1	257-098-5	01-2119457554-33
CI 77266 (nano)	no hazardous substance		1333-86-4	215-609-9	01-2119384822-32
CI 77742	no hazardous substance		10101-66-3	233-257-4	01-2119973495-24
CI 19140	no hazardous substance	< 2 %	12225-21-7	235-428-9	01-2119950328-34
CI 77000	Water React. 2; H261 Flam. Sol. 1; H228	0.1 %	7429-90-5	231-072-3	01-2119529243-45
Polylactic Acid	no hazardous substance	> 95.9 %	9051-89-2	618-575-7	no registration

*) Formulation: 0.8 % Phenyl Methicone CAS# 31230-04-3 / 0.6 % Polyvinyl Alcohol CAS# 9002-89-5 / 0.6 % Polyvinyl Butyral CAS# 63148-65-2

4. First-aid measures

4.1 Description of first aid measures

4.1.1 General Advice

After contact with the melted product contaminated clothes need to be changed. In case of fainting, place and transport the person into recovery position. In case of persisting discomfort please contact a physician. To helpers: Please protect yourself.

4.1.2 After Inhalation

After inhalation of dust particles and in particular decomposition gases, take the injured person into fresh air, lay him down and protect him from hypothermia. In case of a fainting spell and existing breathing, place the person in a stabilized side position. Please contact a physician for treatments.

4.1.3 After Skin Contact

In case of contact with the melted product rinse water over the affected areas of skin for at least 15 minutes. Remove contaminated clothes, but do not remove product residues from the skin. Burns have to be covered with sterile bandages. In case of burns, skin irritations or other symptoms please contact a physician.

4.1.4 After Eye Contact

Remove particle carefully from the affected eye. If needed, remove contact lens. Rinse eye 15 minutes thoroughly with plenty of water. Consult a physician if needed.



According to Attachment II EC Reg. 1907/2006 (REACH)

SILIGIAM N	IATURE -	Type P Co	olor shades	
First created on:	2017-02-14	Updated on:	2022-03-23	
Next inspection on:	2022-12-31	Printed on:	2022-03-23	Version: V4/2022

4.1.5 After Swallowing

Rinse mouth thoroughly and drink plenty of water. In case of indisposition call a physician.

4.2. <u>Main acute and delayed symptoms and effects</u> No information available.

4.3. Advise to the physician

Toxic effects of the product itself except for thermal decomposition and fire are unknown. In case of any discomforts please treat symptomatically.

5. Firefighting actions

5.1 Extinguishing agents

5.1.1 Suitable extinguishing agents: The product itself is neither combustible nor explosive. Extinguishing agents have to be coordinated with the surrounding fire.

- 5.1.2 For safety reason unsuitable extinguishing agents Jet of water.
- 5.2. <u>Special hazards arising from the substance or mixture</u> Carbon monoxides (CO) and other toxic and flammable gases can be released.

5.3. Special protective equipment

An independent respiratory device (isolation device) should be used.

5.4. Additional advice

The product can ignite in case of fire and can continue to burn outside of the source of ignition. Toxic-, flammable gases and vapours can be released through thermal decomposition. It is possible that flames can spread through spontaneous ignition of gaseous decomposition products. Please cool the melted product with water. Collect the burn residues and water for firefighting in compliance with the legal regulations.

6. Measures by accidental release

6.1. <u>Personal precautions, protective equipment and emergency procedures</u> Avoid formation of dust, do not inhale dust. Keep sources of ignition away from the dust.

6.2. Environmental measures

Wastewater must be mechanically cleaned from rest products prior to emptying into the sewer system.

6.3. <u>Cleaning procedures and absorption</u>

Dry absorption and if possible, re-utilisation of the material.

6.4. <u>Reference to other sections</u>

Personal protective equipment according to section 8.2, disposal according to section 13.





According to Attachment II EC Reg. 1907/2006 (REACH)

SiLiglam NATURE - Type P Color shades First created on: 2017-02-14 Updated on: 2022-03-23 Next inspection on: 2022-12-31 Printed on: 2022-03-23

Version: V4/2022

7. Handling and storage

7.1. Protective measures for safe handling

7.1.1 Safety advice

5

Avoid overheating through improper processing and dusting.

7.1.2 Technical protective measures

Local ventilation and airing guarantee, that all limits mentioned under point 8.1 are maintained.

7.1.3 Fire and explosion protection information

Keep away from sources of ignition.

- 7.2. Conditions for safe storage under consideration of incompatibilities
- 7.2.1 Requirements for storage in rooms and containers No special storage necessary. Storage in tightly closed (original) container.

7.2.2 Additional details regarding storage Protect from heat. Comply with the appropriate regulations of the company's fire prevention measures.

- **7.2.3 Information on storage in one common storage facility:** Storage class according to TRGS 510: LGK 11 (flammable solid materials). No incompatible products to mention.
- 7.3. <u>Specific end uses</u> See section 1.2.

8. Exposure limits and personal protection

8.1 <u>Parameters to be monitored</u>

Mechanical dry processing of the product can generate a risk of dust: The local limits of dust concentration at the work have to be considered.

Parameter	CAS-Number	EINECS	Value	Type of limit
General dust limit				Limit at work (AGW) according to the TRGS 900 Regulation
Aluminum	7429-90-5		50 μg/g Kreatinin	Limit at work (BGW) according to the TRGS 903 Regulation

8.2 Exposure controls and monitoring

8.2.1 <u>Technical protection measures</u>

An on-site extraction system is required in the event of gathered dust and thermal pollution from the product.



2022-12-31



SiLiglam NATURE - Type P Color shades First created on: 2017-02-14 Updated on: 2022-03-23

Printed on:

Version: V4/2022

8.2.2 Personal protection equipment

8.2.2.1 Respiratory protection



Next inspection on:

Use respiratory protection in the event of dust exposure, e.g. a P1 dust mark that conforms to EN 143 or a half mask with particle filter FFP1 or PP2 conforms to EN 141. Caution! Limited wearing period.

2022-03-23

pirit of

8.2.2.2 Hand protection

Protective gloves are generally not required. In case of constant skin contact, gloves are sufficient for low mechanical and material stress, see also BGR 195, e.g.:



Material thickness Penetration time: Butyl rubber min. 0.4 mm min. 30 min. acc. to DIN EN 374

8.2.2.3 Eye protection



Side-shielded safety goggles that conform to EN 166 are required when carrying out mechanical processing with exposure to dust.

8.2.2.3 Body protection

Safety shoes to wear the product, as well as normal work clothes are sufficient.

8.2.2.4 General industrial safety and hygiene measures

Do not inhale dust. Avoid contact with eyes. Do not eat, drink or smoke while working. Wash hands before breaks and at the end of work.

8.2.3 Limitation and monitoring of environmental exposure

Environmentally hazardous properties of the product are not known, so that the general operational measures for environmental protection are sufficient.

9. Physical and chemical properties

9.1 **General details**

Physical condition:	Solid
Shape:	Glitter particles in hexagonal shape
Odour:	Odourless
Colour:	Various (refer to table regarding colour proportions,
	Chapter 3.3)

Important details regarding health / environmental protection as well as safety 9.2

pH value:	Not applicable
Heat resistance:	60 ° C
Boiling point / boiling range:	Cannot be measured as decomposition occurs first
Flash point:	Not applicable
Ignition temperature:	> 300 ° C
Self-ignition point (Solid/Gas):	Not self-igniting
Blaze properties:	None
Risk of explosion:	Possible dust- or decomposition gas explosion
Vapour pressure:	To be disregarded
Specific weight:	1.20 kg/dm ³
Bulk density:	0.60 kg/dm ³





According to Attachment II EC Reg. 1907/2006 (REACH)

SILIGIAM N	IAIURE -	I ype P C	olor shades	
First created on:	2017-02-14	Updated on:	2022-03-23	
Next inspection on:	2022-12-31	Printed on:	2022-03-23	Version: V4/2022

Water solubility: Partition coefficient n-Octanol/ water: Viscosity: Vapour density: Evaporation speed:

Insoluble in water Not applicable

Not applicable Not applicable Not applicable

9.3 Additional details

There are no further details required regarding safety-relevant parameters.

10. Stability and reactivity

It is recommended to carry out a trial run prior to processing the product.

10.1. Reactivity

Not reactive under the stated conditions of use and storage.

10.2 <u>Conditions to be avoided</u>

Pyrolysis, dangerous decomposition products and dangerous reactions will not occur if the product is used as intended.

10.3 Substances to be avoided Potent acids, bases, and oxidation agents. Protect from temperatures > 150 °C

10.4 Dangerous decomposition products when heated Aldehyde, carbon monoxide, carbon dioxide, hydrocarbons.

11. Toxicological data

11.1. Information on toxicological effects

- **11.1.1 Toxicokinetic, metabolism and distribution** No data available.
- 11.1.2 Acute toxicity

No data available.

11.1.3 Etching and irritant effects

The contact with the melted product can cause burn wounds. The inhalation of dust and decomposition gases can cause health defects.

11.1.4 Sensitizing effects

No sensitizing effects on skin and respiratory organs known.

- **11.1.5 Specific organ toxicity at single or repeated exposure** No organ toxic effects known.
- **11.1.6 Carcinogenicity, mutagenicity, and reproductive toxicity** No carcinogenic, mutagenic, or toxic to reproduction effects known.





SiLiglam NATURE - Type P Color shades First created on: 2017-02-14 Updated on: 2022-03-23 Next inspection on: 2022-12-31 Printed on: 2022-03-23

Version: V4/2022

12. Environmental details

12.1. Toxicity

No data available.

12.2. Persistence and degradability

The product is insoluble and the inorganic substances it contains are not bioavailable.

12.3. Bioaccumulation potential

The product is insoluble and the inorganic substances it contains are not bioavailable, thus not bio accumulative.

12.4. Mobility in the ground

The product is insoluble and therefore not mobile.

12.5. Other adverse effects

Ozone depletion potential and greenhouse effect are not known.

Ecological and ecotoxicological data are not available. A threat to the environment is not to be expected if the product is handled and disposed of safely.

13. Notes on disposal

13.1 <u>Waste treatment process</u>

The product does not generate any waste that is subject to monitoring in accordance with Regulation (EU) No. 1357/2014. For disposal, national laws and local regulations must be observed.

13.1.1 Product

14.

Product residues should be reused wherever possible.

13.1.2 Uncleaned packaging

Information on Transport

Recommendation: Non-contaminated packaging can be reused. Cleaning agent Water.

14.1	<u>UN-Number</u>	not relevant
14.2.	Proper UN shipping name	not relevant
14.3.	Transport hazard classes	not relevant
14.4.	Packaging group	not relevant
14.5.	Environmental hazards	see section 14
14.6.	Special precautions for the user	see section 7
147	Transport in bulk in accordance with Annov II	

14.7. <u>Transport in bulk in accordance with Annex II</u> to the MARPOL Convention and the IBC Code not relevant

Note: No dangerous goods as defined by ADR/RID/ADN/GGVSEB, ICAO/IATA, IMDG.





According to Attachment II EC Reg. 1907/2006 (REACH)

SiLiglam NATURE - Type P Color shades First created on: 2017-02-14 Updated on: Next inspection on: 2022-12-31 Printed on:

2022-03-23 2022-03-23

Version: V4/2022

15. Legal provisions

15.1 Safety, health, and environmental protection/legislation specific to the substance or mixture

15.1.1 EU-regulations Classification and labelling:	None according to Directive (EC) No. 1272/2008 (CLP) or other known EU regulations.
15.1.2 National regulations Classification and labelling:	None according to the Hazardous Substances Ordinance (GefStoffV) or according to other known national regulations
Employment restrictions:	None according to GefStoffV, JArbSchG or MuSchV
Major Accidents Ordinance:	The product is not subject to the Major Accidents Ordinance.
Water hazard class:	No WGK, not hazardous to water according to AwSV.

16. Additional information

16.1 Summary of H-Statements (chapter 3.3)

- H228 Flammable solid
- H261 In contact with water releases flammable gases
- May cause long lasting harmful effects to aquatic life H413

Recommended Limitations of Use 16.2

SiLiglam is not a toy and must therefore be stored away from children. A resale as toy requires the EC conformity evaluation and the distributor's compliance with the legal regulations. We expressly point out, that a conformity evaluation in this sense has not been carried out by us.

16.2 **Further information**

Sigmund Lindner GmbH Company details: Oberwarmensteinacher Str. 38 95485 Warmensteinach / GERMANY Phone: +49-9277-9940 Fax: +49-9277-99499 Web: www.sili.eu Technical contacts: Mr. Erwin Pschierer (Product Manager Glitter) information Mrs. Manuela Pilz (Product Manager Glitter)





SiLiglam N	ATURE -	Type P C	olor shades
First created on:	2017-02-14	Updated on:	2022-03-23
Next inspection on:	2022-12-31	Printed on:	2022-03-23

Version: V4/2022

16.4 Used abbreviations

A:	Alveolar Dust
ADR:	Accord européen relative au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW:	Occupational exposure limit according to TRGS 900
BGW:	Biological limit value according to TRGS 903
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
CI Nº:	Color Index Number
CLP:	Classification, Labelling and Packaging of Substances and Mixtures
E:	Inhalable Dust
EC Nº:	EINECS Number (European Inventory of Existing Commercial Chemical Substances)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
IATA:	International Air Transport Association
ICAO:	International Civil Aviation Organization
IMDG:	International Maritime Code for Dangerous Goods
REACH:	Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals.
RID:	Règlement concernant le transport international ferroviaire des
	marchandises dangereuses (Regulations Concerning the International
	Transport of Dangerous Goods by Rail)
TRGS:	Technical Rules for Hazardous Substances
WGK:	Water hazard class

16.5 Remarks

All details noted in this data sheet correspond to our knowledge at the time this data sheet has been put into effect. This information should be used as a guideline for a safe treatment in accordance with the products mentioned in our material safety data sheet, during storage, production, transport, and disposal. This information is not applicable to other products, to newly produced materials, if the product mentioned in this material safety data sheet is mixed or blended with other articles or when other transformations are made to it.

Date of the current version:	2022-03-23
Reason for the current version:	adjustment of hazardous classification information
Replaced issue:	MSDS en SiLiglam NATURE Type P Color shades V3/2021